

# Lexmark C522n Colour Printer



# Innovative



20 ppm monochrome and 20 ppm colour

4800 Colour Quality for vibrant colour images and business graphics

New Spherical Chemical Toner for vivid graphic designs

100% front access for all supplies

**LEXMARK**<sup>TM</sup>



- Up to 20 ppm
- 100% front access for all supplies
- 4800 colour quality
- TTFP as fast as 13 seconds

# Lexmark C522n

	<b>Lexmark C522n, C522tn</b>
<b>Part Number</b>	22H0050 (C522n), 22H0076 (C522tn)
<b>Technology</b>	Colour Tandem Laser
<b>Speed</b>	Up to 20 ppm colour and mono
<b>Resolution</b>	4800 Colour Quality, 1200 x 1200 dpi
<b>Time to First Page</b>	As fast as 13 seconds (colour and mono)
<b>Processor</b>	313 MHz
<b>Memory (std./max.)</b>	128MB/640MB
<b>Connectivity</b> Standard: Optional:	USB port and 10BaseT/100BaseTx Ethernet External print servers connecting via parallel or USB port depending on print server model.
<b>Operating Systems</b>	Windows, Linux, UNIX, Mac, NetWare, Server 2003 and OS/400 For a complete list, visit <a href="http://www.lexmark.ca">www.lexmark.ca</a>
<b>Emulations</b>	PostScript 3 emulation, PCL 6 (XL) emulation, PPDS Migration tool, PCL 5e Emulation, PDF 1.5
<b>Fonts</b>	PostScript 3 emulation, 91 scalable PCL 6 emulation, 89 scalable – 2 bitmapped PPDS Migration Tool, 39 scalable – 5 bitmapped
<b>Paper Capacity</b> Standard (in/out) Maximum (in/out)	n: 250 + 1/250; tn: 750 + 1/250 (250 + 500 + 1/250) 750 + 1/250 (250 + 500 + 1/250)
<b>Paper Options</b>	Input: 500-sheet drawer
<b>Paper Sources</b> Standard (in/out) Maximum (in/out)	2/1(n); 3/1(tn) 3/1
<b>Media Types</b>	Plain paper, glossy paper, bond, banner, transparencies, labels, cardstock
<b>Media Sizes</b>	A5, JIS B5, JIS B5, Statement, Folio, Letter, Legal, Executive, A4, Envelopes (7 3/4, 9, 10, DL, C5, B5)
<b>Media Weights</b>	Standard Trays: 16-47 lb (60-177 g/m <sup>2</sup> ) Multi-purpose Feeder: 20-47 lb (75-177 g/m <sup>2</sup> )
<b>Size/Weight</b>	C522n: 17.3" x 16.1" x 19" (W x D x H) (440 mm x 408 mm x 484 mm), 57.5 lb (26.1kg) C522tn: 17.3" x 22" x 24" (W x D x H) (440mm x 558mm x 610mm) 64.8 lb (29.5kg)
<b>Acoustics</b>	Less than 51 dBA printing; Less than 32 dBA idle
<b>Supplies<sup>1</sup></b>	Ships with: 1,500-page Starter Print Cartridge Black, Cyan, Magenta and Yellow Optional supplies: 4,000-page Print Cartridge Black 3,000-page Cyan, Magenta and Yellow 4,000-page Return Program Print Cartridge Black 3,000-page Return Program Print Cartridge Cyan, Magenta and Yellow 20,000-page Photoconductor
<b>Duty Cycle</b>	Up to 45,000 pages per month
<b>Warranty</b>	1-year LexOnSite Repair

<b>Print Cartridges<sup>1</sup></b>	<b>Part No.</b>
3,000-page Cyan Print Cartridge	C5222CS
3,000-page Magenta Print Cartridge	C5222MS
3,000-page Yellow Print Cartridge	C5222YS
4,000-page Black Print Cartridge	C5222KS
4,000-page Return Program Print Cartridge (K)	C5220KS
3,000-page Return Program Print Cartridge (C)	C5220CS
3,000-page Return Program Print Cartridge (M)	C5220MS
3,000-page Return Program Print Cartridge (Y)	C5220YS
<b>Other Supplies</b>	
20,000-page Colour Photo Conductor Kit	C52030X
30,000-page Waste Toner Bottle	C52025X
<b>Media</b>	
Glossy Paper (A4)	12A5951
Glossy Paper (Letter)	12A5950
Transparency (Letter)	12A8540
Transparency (A4)	12A8241
<b>Paper Handling</b>	
500-sheet Drawer	18B2100

<b>Memory Options</b>	<b>Part No.</b>
128MB SDRAM	13N1523
256MB SDRAM	13N1524
512MB DDR-DRAM	13N1526
32MB Flash Card	1021208
64MB Flash Card	1021209
<b>Font Options</b>	
Korean Font DIMM	1021240
Simplified Chinese Font DIMM	1021241
Traditional Chinese Font DIMM	1021242
Japanese Font DIMM	1021243
<b>External Print Servers</b>	
N4000e External Print Server Ethernet 10/100BaseTX – 1-port	14T0030
N4050e 802.11g Wireless Print Server	14T0145
MarkNet X2030t Token -Ring - 3 port	46D000
<b>Adapters</b>	
802.11g Wireless Print Adapter <sup>2</sup>	1010043
<b>Cables</b>	
Parallel (10') Cable	1021231
Serial (50') Cable	1038693
USB (2-meter) Cable	1021294

<sup>1</sup>Yield is based on approximately 5% print coverage

<sup>2</sup>Requires network connectivity